

Heavy Duty O₂ Pressure Regulator

For the Emergency Professionals



FEATURES

All-brass body designed for superior safety and durability. Experience unmatched performance with our new heavy-duty oxygen regulator, designed to outperform the competition. Here's why it's the top choice for your emergency requirements:

- Body is engineered for maximum strength, ensuring longevity and reliability even in the toughest environments.
- 5-year limited warranty, showcasing our confidence in the product's quality and performance.
- Low-profile pressure gauge is shock-resistant and protected by metal casing.
- 2 DISS check valves.
- Precise control over 11 flow positions by adjusting the metal flow knob.

Provides regulated pressure and flow for the operation of 2 demand valves, or 1 demand valve and 1 aspirator. A DISS barb adjustable flow outlet allows attachment of a disposable mask, cannula or bag mask resuscitator. All three outlet configurations may be operated simultaneously.



Item Number

R1836GBHF-25GP

SPECIFICATIONS

Supply Pressure	500 to 2200 psi
Outlet Pressure	High flow outlets: 40 to 60 psi at 500 to 2200 psi inlet pressure
Flow Capacity	High flow outlets: 125 lpm minimum single or combined flow with 500 psi inlet pressure. Constant flow outlet selections: 0-25 lpm: 0, ¼, ½, 1, 2, 3, 4, 6, 8, 10, 15, 25
Filter	20 micron sintered bronze
Safety Relief Pressure	75 to 125 psi
Operating Temperature	-30° F to 125° F
Storage Temperature	-20° F to 120° F
Materials	Body: Chrome-plated brass Knob: Anodized aluminum Outlets: Nickel-plated brass Internal parts: Brass, stainless steel, Viton®, silicon and Teflon®



Item Number
R1836GBHF-25GP

⚠ WARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov